



SINGLE EXTRUDER DOUBLE DIE EXTRUSION COATING PLANT MODEL RPM - 90/1000mm



Remica Two Station
Automatic Surface Winder



Online Trimming

SIZE	RLAM- 6 FT	RLAM- 8 FT
SCREW DIA	80 MM	90 MM
L/D RATIO	1:30	1:30
T-DIE SIZE	900MM X 2 NOS	1000MM X 2 NOS
COATING WIDTH	400MM -800 MM	400 MM-900 MM
MAIN MOTOR	30 HP	40 HP
LAMINA FOR UNIT	7.5 HP	7.5 HP
WINDER	3 HP	5 HP
WEB UNIT	0.5 HP	0.5 HP
HEATING LOAD	40 KW	40 KW
TOTAL POWER APPROX	75 KW	87 KW
MAX OUT PUT	120 TO 150 KG/HR	120 TO 150 KG/HR
MATERIAL	LL / LLDE /PP	LL / LLDE
MAX LINE SPEED	125 MTR / MINUTE	125 MTR/MINUTE
SPACE L x W x H	50 ft x 28 ft x 12ft	50 ft x 28 ft x 12ft

FEATURES

- 5 Layer coating in single process.
- reduce wastage % on PP fabric with printed BOPP LAMINATION.
- smooth and speedy registration control system in bothside bopp printed film lamination.
- energy and space saving
- reduce machinery cost against the tandum lamination
- simple to operate and maintain.
- synchronisation with master control.
- onling trimmer

Application

- PP Fabric With BOPP Printed Film Lamination Both Side Simultaneously For Rice/ Wheat And Other Packaging Bag And Also For Other Branded Packaging Of 5, 10, 15 And 25 Kg.
- Sandwich Lamination Of Fabric / Non - Woven /BOPP/ Paper / Kraft / Aluminum Foil Etc..

Technical data subject to change without notice due to continuous development. Refer our quotation for details.



YouTube Link